

XTeer AW VG 15, 32, 46, 68, 100

Description

XTeer AW is the best anti-wear hydraulic oil. It is formulated with excellent quality base oil technology and an additive system that provides exceptional oxidation stability, water separability and foam suppression. It is especially exceptional for anti-wear protection.

Application

Recommended for applications calling for anti-wear, rust and oxidation inhibited Additives including

- Hydraulic systems
- Industrial bearings
- Circulating systems, splash, bath and ring lube systems for bearings and gears
- A myriad of assorted industrial applications: hoists, machine tools, etc.
- Gear sets not requiring an EP gear oil
- Bath, splash circulating or mist systems

Features / Benefits

- Protection against oxidation
- Low foaming
- Protection against rust and corrosion
- Outstanding wear protection.

Remarks

XTeer AW meets or exceeds the requirements of

- Parker Denison HF-0 (AW 32, 46, 68)
- Fives Cincinnati P-68 (AW 32), P-70 (AW 46), P-69 (AW 68)
- JCMAS HK (AW 32, 46)
- GM LS-2 LH-04 (AW 32, 46, 68)
- Bosch Rexroth RE 90220
- DIN 51524 Part 2,
- ISO 11158 (HM),
- SAE MS 1004 (HM)
- Eaton Brochure 03-401-2010

XTeer AW VG	Density (15°C, kg/m ³)	Viscosity		Viscosity Index	Flash Point (°C)	Pour Point (°C)
		40°C	100°C			
15	862.9	15.3	3.45	100	178	-40
32	864.2	32.2	5.53	108	224	-40
46	860.0	45.0	6.87	109	230	-37.5
68	871.2	68.6	9.15	109	240	-37.5
100	873.0	96.0	11.3	104	244	-35